


1. What type of network cable is used between a terminal and a console port?
cross-over
straight-through
rollover
patch cable

2.



Refer to the exhibit. A network administrator has decided to use packet capture software to evaluate all traffic from the student subnet on the way to the Internet. To ensure that all packets are captured, what network device should be used to connect the monitoring station to the network between R1 and R2?

hub

- router
- firewall appliance
- wireless access point

3. Which three statements are true about the role of routers in the network? (Choose three.)

- They propagate broadcasts.
- They enlarge collision domains.

They segment broadcast domains.

They interconnect different network technologies.

Each router interface requires a separate network or subnet.

They maintain a common frame format between LAN and WAN interfaces.

4. A network administrator is required to use media in the network that can run up to 100 meters in cable length without using repeaters. The chosen media must be inexpensive and easily installed. The installation will be in a pre-existing building with limited cabling space. Which type of media would best meet these requirements?

STP

UTP

- coaxial
- single-mode fiber
- multimode fiber

5. Which three types of connectors are commonly associated with Cisco's V.35 serial cables? (Choose three.)

RJ 11

DB 60


Winchester 15 pin

DB 9

smart serial

RJ 45

6.



Refer to the exhibit. Which three statements identify the type of cabling that would be used in the segments that are shown? (Choose three.)

Segment 1 uses backbone cabling.

Segment 1 uses a patch cable.

Segment 3 uses patch cabling.

Segment 3 uses vertical cabling.

Segment 3 uses horizontal cabling.

Segment 4 uses vertical cabling.

7. A company is planning to subnet its network for a maximum of 27 hosts. Which subnet mask would provide the needed hosts and leave the fewest unused addresses in each subnet?

255.255.255.0

255.255.255.192

255.255.255.224

255.255.255.240

255.255.255.248

8. What does the term "attenuation" mean in data communication?

loss of signal strength as distance increases

time for a signal to reach its destination

leakage of signals from one cable pair to another

strengthening of a signal by a networking device

9. How many host addresses may be assigned on each subnetwork when using the 130.68.0.0 network address with a subnet mask of 255.255.248.0?

30

256


2046

2048

4094

4096

10.



Refer to the exhibit. A student is setting up a home network primarily used for extensive file transfers, streaming video, and gaming. Which network device is best suited to these types of activities in the topology shown?


wireless access point

router

hub

switch

11.



Refer to the exhibit. Assume that all devices are using default settings. How many subnets are required to address the topology that is shown?

1

3

4

5

7

12. Which device is used to create or divide broadcast domains?

hub


switch

bridge

router

repeater


13.



Refer to the exhibit. A network technician has been allocated the 192.168.1.0/24 private IP address range for use in the network that is shown in the exhibit. Which subnet mask would be used to meet the host requirements for segment A of this internetwork?

- 255.255.255.128
- 255.255.255.192
- 255.255.255.224**
- 255.255.255.240
- 255.255.255.248


14.



Refer to the exhibit. Based on the IP configuration shown, what would be the result of Host A and Host B attempting to communicate outside the network segment?

- both host A and B would be successful
- host A would be successful, host B would fail
- host B would be successful, host A would fail**
- both Host A and B would fail

15.



Refer to the exhibit. How many subnets are required to support the network that is shown?

2

3

4

5

16. To establish a console connection from a computer to a Cisco router, which cable wiring option would be used?


crossover cable

straight through cable

rollover cable

V.35 cable

17.



Refer to the exhibit. What destination IP address will PC1 place in the header for a packet destined for PC2?

192.168.1.1

192.168.2.1

192.168.2.2

192.168.3.1

192.168.3.54

18. What are two common methods for setting a UTP Ethernet port to MDI or MDIX operation? (Choose two.)

cable color code association

cable selection and configuration

use of cable testers to determine pinouts

the automatic detection and negotiating of MDI/MDIX operation of the port

the enabling of the mechanism to electrically swap the transmit and receive pairs

19. Which subnet mask would be assigned to the network address of 192.168.32.0 to provide 254 useable host addresses per subnetwork?

255.255.0.0

255.255.255.0

255.255.254.0

255.255.248.0

20. Which option identifies the primary interface which would be used for initial configuration of a Cisco router?


AUX interface

Ethernet interface

serial interface

console interface

21.



Refer to the exhibit. Which three statements are true about the exhibited topology? (Choose three.)

Hosts B and C are in the same subnet.

Five broadcast domains are present.

Host B is using a crossover cable to connect to the router.

Four broadcast domains are present.

Five networks are shown.

Host B is using a rollover cable to connect to the router.

22. What makes fiber preferable to copper cabling for interconnecting buildings? (Choose three.)

greater distances per cable run

durable connections

easily terminated

lower installation cost

greater bandwidth potential

limited susceptibility to EMI/RFI